

SUBMERSIBLE INSTALLATION AIDS

4 - 15 - 00

DEAN BENNETT SUPPLY CO.

Toll Free : 800-621-4291

1770 East 69th Ave. Denver, CO. 80229

Local Phone : 286-1500 FAX 286-0001

Page 19



\$ 11.95

1X9S80DPWPC

1" x 9' SPECIAL SUBMERSIBLE DROP PIPE

We have designed this pipe for our Do-It-Yourself submersible installers. Made from extra heavy 1" Sch 80 PVC plastic pipe and threaded in special 9' short lengths to make for easier installation by an individual. Each length has the 1" Sch 80 threaded PVC drop pipe coupling already attached to the pipe.

This rigid PVC plastic drop pipe will install like galvanized steel pipe and can be used with confidence down to 300' depths, yet this pipe weighs only 25% as much as steel pipe (only 4/10ths lbs per ft) and has much greater corrosion resistance than galvanized pipe. Best of all this pipe can ship via U.P.S. right to your door.



\$ 49.95

10SHROUD

12SHROUD

20SHROUD

SUBMERSIBLE PUMP FLOW INDUCER SLEEVE

When installing a submersible pump in an open body of water or a large diameter well, Franklin Electric requires the use of a flow inducer sleeve to channel water past the motor to provide cooling. Without this sleeve, the motor does not get the cooling effect of the water rushing past it. Our flow inducer sleeves are made of PVC pipe with plastic standoffs to keep the motor centered in the sleeve. A well seal closes the top of the sleeve and provides an opening for your pump drop pipe to exit. Specify drop pipe size being used.

\$ 109.00

10SHROUD&
SCREEN

SUBMERSIBLE PUMP SCREEN / STRAINER

Sand is a problem with every water pump on the market. Failures due to sand affects your warranty and therefore must be protected against. Use our pump shroud with screens to protect your pump from sand or other sediment in the well. Made from the flow inducer units above with 2 snap together lengths of Certaineed PVC 4" continuous slot, molded well screen with a snap on bottom end cap. The top of the shroud is closed with a well seal with an opening for your pump drop pipe. These are available in .012" (12/1000 inch) slot size, which equals 10.3 square inches of open area per setting foot of screen, and 2 screens allow about 10 gallons per minute through.. We also offer these screens in .023" (23/1000 inch) slot size, which equals 19.8 square inches of open area per setting foot of screen, and 2 lengths of screen allow about 18.5 gallons per minute through. Minimum well casing ID must be 5" to use these submersible pump sand protector screens. Specify drop pipe size being used. If you require a strainer longer than the standard model (for larger horsepower submersibles or more gallons of water needed), add 18" long snap on sections to the above unit for \$ 19.50 each.

FREIGHT IS NOT PAID ON PIPE